

**Коммутационный шнур NETLAN U/UTP 4
пары, Кат.5е (Класс D), 100МГц,
2xRJ45/8P8C, T568B, заливной,
многожильный, ВС (чистая медь), PVC
нг(В), серый**

Ordering Table

P/N	Construction	Cat.	Length, m	QTY in group bag Transport box		Size, mm	Mass, kg
				QTY			

**Коммутационный шнур NETLAN U/UTP 4
пары, Кат.5е (Класс D), 100МГц,
2xRJ45/8P8C, T568B, заливной,
многожильный, ВС (чистая медь), PVC
нг(В), серый**

Detailed characteristics

Characteristic	Value
Category	5e
Bandwidth, MHz	100
Construction	U/UTP
Twisted pairs number	4
Conductors material	Bare copper
Conductors type	Stranded
Diameter of wire	7x0, 165±0,01 (26 AWG)
Conductors insulation material	PE
Outer jacket material, mm	5,5±0,03
Jacket color	Grey
Standard compliance	Meets the standards requirements: ISO/IEC 11801, EN 50173 and TIA/EIA-568
Application supporters	10BASE-T, 100BASE-TX, 100BASE-T4, 1000BASE-T, ATM-25, ATM-51, ATM-155, 100VG-AnyLan, TR-4, TR-16 Active, TR-16 Passive
Temperature ranges °C	Storage from -20 to +60. Installation from 0 to +50. Exploitation from -20 to +60
Package	PE package 10 pcs (group PE package include 10 or 5 individual PE packages)
Warranty	1 year
Connectors type	2xRJ45/8P8C
Wiring	T568B
Boot type	+
Jacket material	PVC